

# Wash Down Back Light 8"x12" Series


**ELECTRICAL:**

Input Voltage: 24VDC (25VDC Maximum)  
 Input Current: **-470** 2.8A typical (3.4A Maximum); **-530** 1.6A typical (1.9A Maximum)  
**-660** 1.9A typical (2.4A Maximum); **-880** 2.4A typical (2.9A Maximum)  
**-WHI** 1.8A typical (1.9A Maximum)

Connector: Quick Connect, 4 pin Euro / Micro

Wiring:

Pin #	Wire Color	Function
1	Brown	+24VDC
2	N/C	N/C
3	Blue	+24VDC return (GND)
4	Black	PNP STROBE INPUT: < 1 VDC for "OFF" +24VDC for "ON"



**MECHANICAL:**

Dimensions: <http://www.spectrumillumination.com>

IPC-68 rated Enclosure  
 USFDA compliant enclosure, gaskets and hardware  
 316 Stainless Steel  
 Acrylic Diffuser  
 White Nitril Gaskets

**ILLUMINATION:**

Light Source: LED – 4 Colors, IR  
 Quantity LED's: 1152  
 Light Emitting Pattern: 8" x 12" / 203mm x 304mm  
 LED Life: up to 50,000 hours\*.  
 \*Contact us for LED life information




**PART NUMBER DESIGNATION:**

**WBL812-XXX**

XXX = Light Color -470, -530, -660, -880 & -WHI

Color	Dash #	$\lambda$ Dominant Typical	$\lambda$ Dominant Range	Spectral Half-width $\Delta\lambda_{1/2}$	$\lambda$ Peak Typical	Units
Infrared	-880	n/a	n/a	50	880	nm
Red	-660	643	n/a	20	660	nm
Green	-530	525	520-535	35	530	nm
Blue	-470	470	465-475	25	468	nm
White	-WHI	Color Temp 6300K typ (5600K to 7000K)				



Light includes 4 meter cable, 8, 15 and 30 meter cables are available at additional cost