



LINEAR LIGHT

MLL1103.5-XXX



ELECTRICAL:

Input Voltage: See _LDM3500 spec <http://spectrumillumination.com/product-type/controllers/>
Input Current: See _LDM3500 spec

WARNING !!!

**Use Only Spectrum Illumination LDM Driver with Monster Lights.
Do Not Connect Monster Lights Directly to 24VDC!**

ENVIRONMENTAL:

Operating Temperature: 0 to 50°C
Relative Humidity: 5 to 85% non-condensing

MECHANICAL:

Driver: DIN Rail Mount
Connector: M12 5 pin Reverse Key Euro / Micro
Weight: 32 lbs. (14.5kg)

ILLUMINATION:

Light Source: LED – 11 Colors, UV & IR
Quantity HB LED's: 108
Light Emitting Pattern: 103.5" / 2629mm
LED Life: varies by color, click link below for LED life details:

<http://spectrumillumination.com/wp-content/uploads/LED-life-data.pdf>

PART NUMBER DESIGNATION: MLL1103.5-XXX

XXX = Light Color - 450, 470, 505, 530, 590, 630, 660, 730, WHI, NWH, WWH, 365, 395, 850 & 940

For details on available LED's, please visit link below:

<http://spectrumillumination.com/wp-content/uploads/Monster-LED-Info.pdf>




Light includes LDM DIN rail mount constant current driver, 4-meter cable (driver is available with variable or 0-10VDC intensity control - cable also available in 8, 15 and 30-meter lengths).

Monster Lights have changeable lenses for matching the area of illumination with the working distance



Monster Lenses - P/N MLLD111.5-XXX/XX
12° Narrow (Standard) /16 – 16° Frosted Narrow
/30 – 30° Medium Angle /23 – 23° Frosted Medium
/50 – 50° Medium Angle /39 – 39° Frosted Wide
/F – ~70° Wide Angle /R60 – 60° Reflectors
/L – 44° x 12° Angle /R – 90° Reflectors



*** UV lights are available with narrow, medium and wide silicone lenses, 60° (STD) or 90° reflectors only ***

Spectrum Illumination • 5114 Industrial Park Rd. • Montague, MI 49437
Phone 231-894-4590 • Fax 231-894-4582
www.spectrumillumination.com

Rev. Date: 2020-12-17